

Package: lmerPerm (via r-universe)

July 14, 2026

Type Package

Title Perform Permutation Test on General Linear and Mixed Linear Regression

Version 0.1.9

Description We provide a solution for performing permutation tests on linear and mixed linear regression models. It allows users to obtain accurate p-values without making distributional assumptions about the data. By generating a null distribution of the test statistics through repeated permutations of the response variable, permutation tests provide a powerful alternative to traditional parameter tests (Holt et al. (2023) <[doi:10.1007/s10683-023-09799-6](https://doi.org/10.1007/s10683-023-09799-6)>). In this early version, we focus on the permutation tests over observed t values of beta coefficients, i.e. original t values generated by parameter tests. After generating a null distribution of the test statistic through repeated permutations of the response variable, each observed t values would be compared to the null distribution to generate a p-value. To improve the efficiency, a stop criterion (Anscombe (1953) <[doi:10.1111/j.2517-6161.1953.tb00121.x](https://doi.org/10.1111/j.2517-6161.1953.tb00121.x)>) is adopted to force permutation to stop if the estimated standard deviation of the value falls below a fraction of the estimated p-value. By doing so, we avoid the need for massive calculations in exact permutation methods while still generating stable and accurate p-values.

License GPL-3

Encoding UTF-8

Imports lmerTest,stats

RoxygenNote 7.2.3

NeedsCompilation no

Author Wentao Zeng [aut, cre, cph]

Maintainer Wentao Zeng <wentaozeng@aliyun.com>

Config/pak/sysreqs cmake make

Repository <https://awquinlan.r-universe.dev>
Date/Publication 2023-04-18 13:10:06 UTC
RemoteUrl <https://github.com/cran/lmerPerm>
RemoteRef HEAD
RemoteSha 7cb2b9e6ecd10bac78efe8962daf3a53d6922407

Contents

lmerp	2
permute_fun	3
s1	3
s2	4
Index	5

lmerp	<i>This function is used for permutation test for general and mixed linear regression</i>
-------	---

Description

perform general and mixed linear regression by lm function in R base or lmer function in lmer/lmertest package and permutation tests on observed t values of beta coef -ficients

Usage

```
lmerp(formula, data, thresh, R, mixed, minimum)
```

Arguments

formula	Regression formula in the form 'y~x1+x2+x3' for general linear function or 'y~x1+x2+x3+(1 x4)' or 'y~x1+x2+x3+(x3 x4)' for mixed linear function
data	A data frame specifying the data to be analysed
thresh	Threshold to stop iteration, default value is 0.1
R	The maximum number of iteration, default value is 1000
mixed	A logic value indicates if you desire to perform mixed linear model or not. De-fault value is FALSE.
minimum	The minimum number of iteration, default value is 50

Value

A list contains 2 items: Results and T_perm, the former contains results of origi -nal parameter test and results of permutation test including adjusted confident interval (Ci_perm), p values (P_perm), iteration number(Iteration), the later contains a list cont -ains all t values generated in each permu-tation

Examples

```
formula<-mpg~cyl
data<-mtcars
my_perm<-lmerp(formula,data)
```

permute_fun

This function defines the permutation strategy

Description

perform permutation on response variable i.e. y, using the stop criterion suggested by Anscombe

Usage

```
permute_fun(data, mle)
```

Arguments

data	A data frame specifying the data to be analysed.
mle	A string that indicated response variable

Value

A data frame containing the data with a permuted y.

Examples

```
data<-mtcars
permute<-permute_fun(data=data,mle='mpg')
```

s1

Return t values of general linear model

Description

perform mixed linear regression in lmer/lmertest package for getting observed t values or permutation test

Usage

```
s1(data, formula)
```

Arguments

data	A dataframe specifying the data to be analysed
formula	A formula in the form like'y~x1+x2+x3 in lm function

Value

An object of class "lm"

Examples

```
data<-mtcars
formula<-mpg~cyl
s1(data=data, formula=formula)
```

s2

Estimate t values of mixed linear model

Description

perform mixed linear regression in lmerTest package for getting observed t values or permutation test

Usage

```
s2(data, formula)
```

Arguments

data	A dataframe specifying the data to be analysed
formula	A formula in the form like 'y~x1+x2+x3+(1 x4)' or like 'y~x1+x2+x3 +(x3 x4)' in lmer function

Value

An object of class "lmerTest"

Examples

```
data<-mtcars
formula<-mpg~cyl+(1|gear)
statistic<-s2(data=data, formula=formula)
```

Index

lmerp, [2](#)

permute_fun, [3](#)

s1, [3](#)

s2, [4](#)